2020 SUPER DUTY F-SERIES TRUCKS

Order Guide Supplemental Reference

9/23/19

This supplement contains Maximum Payload Charts, Snow Plow Application Charts, Cab-to-Axle dimensions and Spring Selection Charts.

This information will help you in selecting the right truck to meet your customers' needs.

Please refer to the appropriate 2020 eSourceBook section for more complete weight rating information.

CONTENTS

Payload Package Selection Charts

F-250 SRW Pickup	1
F-350 SRW Pickup	2
F-350 DRW Pickup	3
F-450 DRW Pickup	4
F-350 SRW Chassis Cab	5
F-350 DRW Chassis Cab	6
F-450 Chassis Cab	7
F-550 Chassis Cab	8
Snow Plow Applications Charts	9
Cab-to-Axle Dimension Chart	10

Front Spring/GAWR Selection Charts

F-250 SRW Pickup	11
F-350 SRW Pickup	12
F-350 DRW Pickup	13
F-450 DRW Pickup	14
F-350 SRW Chassis Cab	15
F-350 DRW Chassis Cab	16
F-450 Chassis Cab	17
F-550 Chassis Cab	18

2020 SUPER DUTY F-SERIES TRUCKS

Maximum Payload Package Selector Charts

9/23/2019

F-250 Pickup
Standard GVWR

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase (in.)		141.6		148.0		164.2		159.8		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	10,000	4,260	10,000	3,980	10,000	3,870	10,000	3,880	10,000	3,650
	7.3L	10,000	4,150	10,000	3,880	10,000	3,770	10,000	3,780	10,000	3,550
	6.7L	10,000	3,450	10,000	3,180	10,000	3,040	10,000	3,060	10,000	2,830
4x4	6.2L	10,000	3,820	10,000	3,550	10,000	3,460	10,000	3,470	10,000	3,210
	7.3L	10,000	3,710	10,000	3,450	10,000	3,360	10,000	3,360	10,000	3,100
	6.7L	10,000	3,030	10,000	2,770	10,000	2,650	10,000	2,660	10,000	2,380

F-250 Pickup
Optional GVWR — Fixed

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase (in.)		141.6		148.0		164.2		159.8		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	9,900	4,160	9,900	3,880	9,900	3,770	9,900	3,780	9,900	3,550
	7.3L	9,900	4,050	9,900	3,780	9,900	3,670	9,900	3,680	9,900	3,450
	6.7L	9,900	3,350	9,900	3,080	9,900	2,940	9,900	2,960	9,900	2,730
4x4	6.2L	9,900	3,720	9,900	3,450	9,900	3,360	9,900	3,370	9,900	3,110
	7.3L	9,900	3,610	9,900	3,350	9,900	3,260	9,900	3,260	9,900	3,000
	6.7L	9,900	2,930	9,900	2,670	9,900	2,550	9,900	2,560	9,900	2,280

F-250 Pickup
Optional GVWR — Variable

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase (in.)		141.6		148.0		164.2		159.8		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.7L	10,600	3,940	10,700	3,770	10,800	3,740	10,800	3,750	10,800	3,520
4x4	6.7L	10,800	3,720	10,800	3,460	10,800	3,310	10,800	3,320	10,800	3,040

2020 SUPER DUTY F-SERIES TRUCKS

Maximum Payload Package Selector Charts

9/23/2019

F-350 SRW Pickup
Standard Variable GVWR for 17" Wheel & Tire

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase (in.)		141.6		148.0		164.2		159.8		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	10,100	4,160	10,100	3,910	10,400	4,090	10,200	3,850	10,600	4,020
	7.3L	10,100	4,120	10,100	3,870	10,400	4,060	10,200	3,810	10,600	3,980
	6.7L	10,600	3,930	10,700	3,800	11,000	3,980	10,800	3,720	11,100	3,780
4x4	6.2L	10,400	4,030	10,500	3,870	10,800	4,060	10,600	3,820	10,900	3,890
	7.3L	10,400	3,990	10,500	3,840	10,800	4,030	10,600	3,790	10,900	3,850
	6.7L	11,000	3,910	11,000	3,680	11,300	3,850	11,200	3,700	11,500	3,740

F-350 SRW Pickup
Standard Variable GVWR for 18" Wheel & Tire

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase (in.)		141.6		148.0		164.2		159.8		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	10,500	4,500	10,600	4,350	10,900	4,540	10,700	4,290	11,100	4,460
	7.3L	10,500	4,470	10,600	4,310	10,900	4,500	10,700	4,250	11,100	4,420
	6.7L	11,100	4,380	11,200	4,250	11,500	4,420	11,300	4,160	11,500	4,120
4x4	6.2L	10,900	4,470	11,000	4,320	11,300	4,500	11,100	4,260	11,300	4,230
	7.3L	10,900	4,440	11,000	4,280	11,300	4,470	11,100	4,230	11,300	4,190
	6.7L	11,500	4,350	11,500	4,120	11,500	3,990	11,500	3,940	12,000	4,190

F-350 SRW Pickup
Standard Variable GVWR for 18"/20" All-Terrain & 20" All-Season Tire 4x4

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase (in.)		141.6		148.0		164.2		159.8		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x4	6.2L	11,400	4,960	11,300	4,610	11,500	4,700	11,300	4,460	11,500	4,420
	7.3L	11,400	4,930	11,300	4,580	11,500	4,670	11,300	4,420	11,500	4,390
	6.7L	11,500	4,340	11,500	4,110	11,500	3,990	11,500	3,930	12,400	4,580

F-350 SRW Pickup
Optional Fixed 10,000-lb. GVWR

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase (in.)		141.6		148.0		164.2		159.8		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	10,000	4,060	10,000	3,810	10,000	3,690	10,000	3,650	10,000	3,420
	7.3L	10,000	4,020	10,000	3,770	10,000	3,660	10,000	3,610	10,000	3,380
	6.7L	10,000	3,330	10,000	3,100	10,000	2,980	10,000	2,920	10,000	2,680
4x4	6.2L	10,000	3,630	10,000	3,370	10,000	3,260	10,000	3,220	10,000	2,990
	7.3L	10,000	3,590	10,000	3,340	10,000	3,230	10,000	3,190	10,000	2,950
	6.7L	10,000	2,910	10,000	2,680	10,000	2,550	10,000	2,500	10,000	2,240

F-350 SRW Pickup
Optional Fixed 9900-lb. GVWR (Available in Canada only)

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase (in.)		141.6		148.0		164.2		159.8		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	9,900	3,960	9,900	3,710	9,900	3,590	9,900	3,550	9,900	3,320
	7.3L	9,900	3,920	9,900	3,670	9,900	3,560	9,900	3,510	9,900	3,280
	6.7L	9,900	3,230	9,900	3,000	9,900	2,880	9,900	2,820	9,900	2,580
4x4	6.2L	9,900	3,530	9,900	3,270	9,900	3,160	9,900	3,120	9,900	2,890
	7.3L	9,900	3,490	9,900	3,240	9,900	3,130	9,900	3,090	9,900	2,850
	6.7L	9,900	2,810	9,900	2,580	9,900	2,450	9,900	2,400	9,900	2,140

F-350 SRW Pickup
Optional GVWR Downgrade 18" All-Season Tire

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase (in.)		141.6		148.0		164.2		159.8		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.7L	---	---	---	---	11,400	4,380	---	---	11,400	4,080
4x4	6.2L	---	---	---	---	11,400	4,660	---	---	11,400	4,390
	7.3L	---	---	---	---	11,400	4,630	---	---	11,400	4,350
	6.7L	11,400	4,310	11,400	4,080	11,400	3,950	11,400	3,900	11,400	3,640

2020 SUPER DUTY F-SERIES TRUCKS

Maximum Payload Package Selector Charts

9/23/2019

F-350 DRW Pickup
Maximum GVWR

Cab		Regular Cab		SuperCab		Crew Cab	
Wheelbase (in.)		141.6		164.2		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	14,000	7,660	14,000	7,190	14,000	6,960
	7.3L	14,000	7,660	14,000	7,190	14,000	6,960
	6.7L	14,000	6,930	14,000	6,470	14,000	6,240
4x4	6.2L	14,000	7,210	14,000	6,760	14,000	6,530
	7.3L	14,000	7,210	14,000	6,770	14,000	6,530
	6.7L	14,000	6,490	14,000	6,050	14,000	5,780

F-350 DRW HD Payload
Maximum GVWR

Cab		Regular Cab		SuperCab		Crew Cab	
Wheelbase (in.)		141.6		164.2		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	14,000	7,850	---	---	---	---
	6.7L	14,000	7,030	---	---	---	---

F-350 DRW Pickup
Optional GVWR Downgrade

Cab		Regular Cab		SuperCab		Crew Cab	
Wheelbase (in.)		141.6		164.2		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	13,000	6,660	13,000	6,190	13,000	5,960
	7.3L	13,000	6,660	13,000	6,190	13,000	5,960
	6.7L	13,000	5,930	13,000	5,470	13,000	5,240
4x4	6.2L	13,000	6,210	13,000	5,760	13,000	5,530
	7.3L	13,000	6,210	13,000	5,770	13,000	5,530
	6.7L	13,000	5,490	13,000	5,050	13,000	4,780

Note: 13,000 GVWR not available on 6.7L Diesel with Pickup Box Delete

2020 SUPER DUTY F-SERIES TRUCKS

Maximum Payload Package Selector Charts

9/23/2019

F-450 DRW Pickup
Standard GVWR

Cab		Regular Cab		Crew Cab	
Wheelbase (in.)		141.6		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.7L	14,000	6,210	14,000	5,630
4x4	6.7L	14,000	5,900	14,000	5,320

2020 SUPER DUTY F-SERIES TRUCKS

Maximum Payload Package Selector Charts

9/23/2019

F-350 SRW Chassis Cab
Optional Fixed 9800-lb. GVWR

		Regular Cab 60" CA		SuperCab 60" CA		Crew Cab 60" CA	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	9,800	4,370	9,800	4,070	9,800	3,830
	7.3L	9,800	4,370	9,800	4,070	9,800	3,830
	6.7L	9,800	3,630	9,800	3,280	9,800	3,040
4x4	6.2L	9,800	3,960	9,800	3,640	9,800	3,420
	7.3L	9,800	3,960	9,800	3,640	9,800	3,420
	6.7L	9,800	3,190	9,800	2,850	9,800	2,620

F-350 SRW Chassis Cab
Optional Fixed 10,000-lb. GVWR

		Regular Cab 60" CA		SuperCab 60" CA		Crew Cab 60" CA	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	10,000	4,520	10,000	4,220	10,000	3,980
	7.3L	10,000	4,520	10,000	4,220	10,000	3,980
	6.7L	10,000	3,780	10,000	3,430	10,000	3,190
4x4	6.2L	10,000	4,110	10,000	3,790	10,000	3,560
	7.3L	10,000	4,110	10,000	3,790	10,000	3,560
	6.7L	10,000	3,340	10,000	2,990	10,000	2,770

F-350 SRW Chassis Cab
Standard/Variable GVWR for 18" Wheels/Tires

		Regular Cab 60" CA		SuperCab 60" CA		Crew Cab 60" CA	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	10,500	4,870	10,900	4,970	11,000	4,830
	7.3L	10,500	4,870	10,900	4,970	11,000	4,830
	6.7L	11,100	4,730	11,500	4,780	11,500	4,540
4x4	6.2L	10,900	4,860	11,300	4,940	11,400	4,820
	7.3L	10,900	4,860	11,300	4,940	11,400	4,820
	6.7L	11,500	4,690	11,500	4,350	11,500	4,120

2020 SUPER DUTY F-SERIES TRUCKS

Maximum Payload Package Selector Charts

9/23/2019

F-350 DRW Chassis Cab
Standard Fixed GVWR

		Regular Cab				SuperCab		Crew Cab	
		60" CA		84" CA		60" CA		60" CA	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	14,000	7,940	14,000	7,900	14,000	7,600	14,000	7,460
	7.3L	14,000	7,940	14,000	7,900	14,000	7,600	14,000	7,460
	6.7L	14,000	7,200	14,000	7,130	14,000	6,850	14,000	6,690
4x4	6.2L	14,000	7,550	14,000	7,500	14,000	7,200	14,000	7,040
	7.3L	14,000	7,550	14,000	7,500	14,000	7,200	14,000	7,040
	6.7L	14,000	6,800	14,000	6,740	14,000	6,450	14,000	6,280

2020 SUPER DUTY F-SERIES TRUCKS

Maximum Payload Package Selector Charts

9/23/2019

F-450 DRW Chassis Cab
Standard Fixed 16,500 GVWR

		Regular Cab								SuperCab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
		GVWR	Payload	GVWR	Payload	GVWR	Payload	GVWR	Payload	GVWR	Payload	GVWR	Payload	GVWR	Payload	GVWR	Payload
Drive	Engine	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)
4x2	7.3L	16,500	9,850	16,500	9,790	16,500	9,610	16,500	9,550	16,500	9,550	16,500	9,360	16,500	9,380	16,500	9,230
	6.7L	16,500	9,110	16,500	9,040	16,500	8,860	16,500	8,800	16,500	8,800	16,500	8,590	16,500	8,650	16,500	8,480
4x4	7.3L	16,500	9,540	16,500	9,450	16,500	9,300	16,500	9,230	16,500	9,190	16,500	9,030	16,500	9,070	16,500	8,940
	6.7L	16,500	8,790	16,500	8,710	16,500	8,550	16,500	8,480	16,500	8,440	16,500	8,270	16,500	8,330	16,500	8,190

F-450 DRW Chassis Cab
Optional Fixed 15,000 GVWR

		Regular Cab								SuperCab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
		GVWR	Max Payload	GVWR	Max Payload	GVWR	Max Payload	GVWR	Max Payload	GVWR	Max Payload	GVWR	Max Payload	GVWR	Max Payload	GVWR	Max Payload
Drive	Engine	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)
4x2	7.3L	15,000	8,350	15,000	8,290	15,000	8,110	15,000	8,050	15,000	8,050	15,000	7,860	15,000	7,880	15,000	7,730
	6.7L	15,000	7,610	15,000	7,540	15,000	7,360	15,000	7,300	15,000	7,300	15,000	7,090	15,000	7,150	15,000	6,980
4x4	7.3L	15,000	8,040	15,000	7,950	15,000	7,800	15,000	7,730	15,000	7,690	15,000	7,530	15,000	7,570	15,000	7,440
	6.7L	15,000	7,290	15,000	7,210	15,000	7,050	15,000	6,980	15,000	6,940	15,000	6,770	15,000	6,830	15,000	6,690

F-450 DRW Chassis Cab
Optional Fixed 16,000 GVWR

		Regular Cab								SuperCab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
		GVWR	Max Payload	GVWR	Max Payload	GVWR	Max Payload	GVWR	Max Payload	GVWR	Max Payload	GVWR	Max Payload	GVWR	Max Payload	GVWR	Max Payload
Drive	Engine	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)	(lbs.)
4x2	7.3L	16,000	9,350	16,000	9,290	16,000	9,110	16,000	9,050	16,000	9,050	16,000	8,860	16,000	8,880	16,000	8,730
	6.7L	16,000	8,610	16,000	8,540	16,000	8,360	16,000	8,300	16,000	8,300	16,000	8,090	16,000	8,150	16,000	7,980
4x4	7.3L	16,000	9,040	16,000	8,950	16,000	8,800	16,000	8,730	16,000	8,690	16,000	8,530	16,000	8,570	16,000	8,440
	6.7L	16,000	8,290	16,000	8,210	16,000	8,050	16,000	7,980	16,000	7,940	16,000	7,770	16,000	7,830	16,000	7,690

2020 SUPER DUTY F-SERIES TRUCKS

Maximum Payload Package Selector Charts

9/23/2019

F-550 DRW Chassis Cab
Standard 18,000 GVWR

		Regular Cab								SuperCab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	7.3L	18,000	11,350	18,000	11,290	18,000	11,110	18,000	11,050	18,000	11,050	18,000	10,860	18,000	10,880	18,000	10,730
	6.7L	18,000	10,610	18,000	10,540	18,000	10,360	18,000	10,300	18,000	10,300	18,000	10,090	18,000	10,150	18,000	9,980
4x4	7.3L	18,000	11,040	18,000	10,950	18,000	10,800	18,000	10,730	18,000	10,690	18,000	10,530	18,000	10,570	18,000	10,440
	6.7L	18,000	10,290	18,000	10,210	18,000	10,050	18,000	9,980	18,000	9,940	18,000	9,770	18,000	9,830	18,000	9,690

F-550 DRW Chassis Cab
Optional 17,500 GVWR

		Regular Cab								SuperCab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	7.3L	17,500	10,850	17,500	10,790	17,500	10,610	17,500	10,550	17,500	10,550	17,500	10,360	17,500	10,380	17,500	10,230
	6.7L	17,500	10,110	17,500	10,040	17,500	9,860	17,500	9,800	17,500	9,800	17,500	9,590	17,500	9,650	17,500	9,480
4x4	7.3L	17,500	10,540	17,500	10,450	17,500	10,300	17,500	10,230	17,500	10,190	17,500	10,030	17,500	10,070	17,500	9,940
	6.7L	17,500	9,790	17,500	9,710	17,500	9,550	17,500	9,480	17,500	9,440	17,500	9,270	17,500	9,330	17,500	9,190

F-550 DRW Chassis Cab
Optional 19,000 GVWR

		Regular Cab								SuperCab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	7.3L	19,000	12,310	---	---	---	---	---	---	---	---	---	---	---	---	---	---
4x4	7.3L	19,000	12,000	---	---	---	---	---	---	---	---	---	---	---	---	---	---

F-550 DRW Chassis Cab
Optional 19,500 GVWR

		Regular Cab								SuperCab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	7.3L	---	---	19,500	12,750	19,500	12,570	19,500	12,510	19,500	12,510	19,500	12,320	19,500	12,340	19,500	12,190
	6.7L	19,500	12,070	19,500	12,000	19,500	11,820	19,500	11,760	19,500	11,760	19,500	11,550	19,500	11,610	19,500	11,440
4x4	7.3L	---	---	19,500	12,410	19,500	12,260	19,500	12,190	19,500	12,150	19,500	11,990	19,500	12,030	19,500	11,900
	6.7L	19,500	11,750	19,500	11,670	19,500	11,510	19,500	11,440	19,500	11,400	19,500	11,230	19,500	11,290	19,500	11,150

2020 SUPER DUTY F-SERIES TRUCKS

Snow Plow Application Charts

9/23/2019

F-250-450 4x4 Pickup/Box Delete Models (with Driver and One Passenger)

Cab	Wheelbase (in.)	Engine	F-250 4x4	F-350 SRW 4x4*	F-350 DRW 4x4	F-450 4x4
Regular Cab	141.6	6.2L V8	100/1300	100/1300	100/1300	X
		7.3L V8	100/1300	100/1300	100/1300	X
		6.7L V8	100/1155	100/1185	100/1190	100/1005
SuperCab	148	6.2L V8	100/1300	100/1285	X	X
		7.3L V8	100/1300	100/1285	X	X
		6.7L V8	100/1005	100/1080	X	X
	164.2	6.2L V8	100/1285	100/1300	100/1300	X
		7.3L V8	100/1280	100/1300	100/1300	X
		6.7L V8	100/905	100/965	100/945	X
Crew Cab	159.8	6.2L V8	100/1300	100/1300	X	X
		7.3L V8	100/1300	100/1300	X	X
		6.7L V8	100/925	100/985	X	X
	176	6.2L V8	100/1300	100/1300	100/1300	X
		7.3L V8	100/1300	100/1300	100/1300	X
		6.7L V8	100/755	100/835	100/815	100/675

Legend: *Considering Std. 17" Tires and max. GAWR. 100/750= Maximum 100 lbs. of permanently attached hardware/maximum 750 lbs. of removable plow blade and hardware. The plow and hardware weight limits are shown based upon a vehicle with 33% Ford option content and 300 lbs. for the driver and front-seat passenger (150. lbs each). This chart ONLY shows maximum recommended values.

X = Not recommended for snow plow application. Snow Plow Package not available.

F-350 4x4 and F-450/F-550 4x2/4x4 Chassis Cab Models (with Driver and One Passenger)

Cab	Wheelbase/ CA (in.)	Engine	F-350 SRW 4X4	F-350 DRW 4x4	F-450 4x2 16,500-lb. GVWR	F-450 4x4 16,500-lb. GVWR	F-550 4x2 18,000-lb. GVWR	F-550 4x4 18,000-lb. GVWR	F-550+ 4x2 19,000/ 19,500-lb. GVWR	F-550+ 4x4 19,000/ 19,500-lb. GVWR
Regular Cab	145/60	6.2L V8	100/1350	100/1350	X	X	X	X	X	X
		7.3L V8	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	100/1225	100/1200	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
	169/84	6.2L V8	X	100/1350	X	X	X	X	X	X
		7.3L V8	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	X	100/1100	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
	191.5/108	6.2L V8	X	X	X	X	X	X	X	X
		7.3L V8	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
	205/120	6.2L V8	X	X	X	X	X	X	X	X
		7.3L V8	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
SuperCab	167.5/60	6.2L V8	100/1350	1001350	X	X	X	X	X	X
		7.3L V8	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	100/1075	100/1075	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
	191.9/84	6.2L V8	X	X	X	X	X	X	X	X
		7.3L V8	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
Crew Cab	179.4/60	6.2L V8	100/1350	100/1350	X	X	X	X	X	X
		7.3L V8	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	100/950	100/975	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
	203.4/84	6.2L V8	X	X	X	X	X	X	X	X
		7.3L V8	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350

Legend: 100/750= Maximum 100 lbs. of permanently attached hardware. Maximum 750 lbs. of removable plow blade and hardware (maximum plow system weight is the sum of these). The plow and hardware weight limits are shown based upon a vehicle with maximum buildable option content and 300. lbs for the driver and front-seat passenger (150. lbs each). This chart ONLY shows maximum recommended values.

X = Unavailable vehicle configuration.

2020 SUPER DUTY F-SERIES TRUCKS

Cab-to-Axle Dimension Chart

9/23/2019

Model	Cab	Wheelbase (in.)	Cab-to-Axle (CA) (in.)	Pickup	Box Delete	Chassis Cab
F-250	Regular Cab	141.6	56.1	8' Box	Yes	--
	SuperCab	148.0	39.9	6.75' Box	--	--
		164.2	56.1	8' Box	Yes	--
	Crew Cab	159.8	39.9	6.75' Box	--	--
		176.0	56.1	8' Box	Yes	--
F-350	Regular Cab	141.6	56.1	8' Box	Yes	--
		145.3	60.0	--	--	Yes
		169.3	84.0	--	--	Yes
	SuperCab	148.0	39.9	6.75' Box	--	--
		164.2	56.1	8' Box	Yes	--
		167.9	60.0	--	--	Yes
	Crew Cab	159.8	39.9	6.75' Box	--	--
		176.0	56.1	8' Box	Yes	--
		179.8	60.0	--	--	Yes
F-450	Regular Cab	141.6	56.1	8' Box	--	--
		145.3	60.0	--	--	Yes
		169.3	84.0	--	--	Yes
		193.3	108.0	--	--	Yes
		205.3	120.0	--	--	Yes
	SuperCab	167.9	60.0	--	--	Yes
		191.9	84.0	--	--	Yes
	Crew Cab	176.0	56.1	8' Box	--	--
		179.8	60.0	--	--	Yes
		203.8	84.0	--	--	Yes
F-550	Regular Cab	145.3	60.0	--	--	Yes
		169.3	84.0	--	--	Yes
		193.3	108.0	--	--	Yes
		205.3	120.0	--	--	Yes
	SuperCab	167.9	60.0	--	--	Yes
		191.9	84.0	--	--	Yes
	Crew Cab	179.8	60.0	--	--	Yes
		203.8	84.0	--	--	Yes

2020 SUPER DUTY F-SERIES TRUCKS

Front GAWR Selection Chart

9/23/2019

F-250 Pickup

Heavy-Service Suspension Package	Front springs/GAWR will be selected 1 upgrade higher than standard computer selection.
Camper Package	4x2: Front springs/GAWR will be selected 2 upgrades higher than standard computer selection.
	4x4: Front springs/GAWR will be selected 1 upgrade higher than standard computer selection.
Snow Plow Package	Front springs/GAWR is assigned or specifically selected as shown in the chart below.

Cab Style Drive/WB (in.)	Engine	Front GAWR (lbs.) Standard		Heavy-Duty Front Suspension Package (lbs.) 5,250-lb. Maximum (4x2) 6,000-lb. Maximum (4x4)	Camper Package (lbs.) 5,250-lb. Maximum (4x2) 6,000-lb. Maximum (4x4)	Snow Plow Package (lbs.)
		Minimum	Maximum			
Regular Cab 4x2/141.6	6.2L	3,800	3,950	1 UP	2 UP	---
	7.3L	3,800	3,950	1 UP	2 UP	---
	6.7L	4,400	4,550	1 UP	2 UP	---
Regular Cab 4x4/141.6	6.2L	4,400	4,400	1 UP	1 UP	5,600
	7.3L	4,400	4,400	1 UP	1 UP	5,600
	6.7L	4,800	4,800	1 UP	1 UP	6,000
SuperCab 4x2/148.0	6.2L	3,800	4,100	1 UP	2 UP	---
	7.3L	3,950	4,250	1 UP	2 UP	---
	6.7L	4,550	4,850	1 UP	2 UP	---
SuperCab 4x2/164.2	6.2L	4,100	4,400	1 UP	2 UP	---
	7.3L	4,250	4,400	1 UP	2 UP	---
	6.7L	4,850	5,000	1 UP	2 UP	---
SuperCab 4x4/148.0	6.2L	4,400	4,800	1 UP	1 UP	5,600
	7.3L	4,400	4,800	1 UP	1 UP	5,600
	6.7L	5,200	5,200	1 UP	1 UP	6,000
SuperCab 4x4/164.2	6.2L	4,800	4,800	1 UP	1 UP	5,600
	7.3L	4,800	4,800	1 UP	1 UP	5,600
	6.7L	5,200	5,600	1 UP	1 UP	6,000
Crew Cab 4x2/159.8	6.2L	3,950	4,250	1 UP	2 UP	---
	7.3L	3,950	4,250	1 UP	2 UP	---
	6.7L	4,700	4,850	1 UP	2 UP	---
Crew Cab 4x2/176.0	6.2L	4,250	4,400	1 UP	2 UP	---
	7.3L	4,250	4,550	1 UP	2 UP	---
	6.7L	4,850	5,250	1 UP	2 UP	---
Crew Cab 4x4/159.8	6.2L	4,400	4,800	1 UP	1 UP	5,600
	7.3L	4400/4800*	4,800	1 UP	1 UP	5,600
	6.7L	5,200	5,200	1 UP	1 UP	6,000
Crew Cab 4x4/176.0	6.2L	4,800	5,200	1 UP	1 UP	6,000
	7.3L	4,800	5,200	1 UP	1 UP	6,000
	6.7L	5,600	5,600	1 UP	1 UP	6,000

*When ordered with ORV Package (17Y — Tremor)
Please refer to the Body Builder's Layout Book for further information regarding front GAWR.

2020 SUPER DUTY F-SERIES TRUCKS

Front GAWR Selection Chart

9/23/2019

F-350 SRW Pickup — Standard/Variable GVWR for 17" Wheel & Tire

Cab Style Drive/WB (in.)	Engine	Front GAWR (lbs.) Standard		Heavy-Duty Front Suspension Package (lbs.) 5,250-lb. Maximum (4x2) 6,000-lb. Maximum (4x4)	Camper Package (lbs.) 5,250-lb. Maximum (4x2) 6,000-lb. Maximum (4x4)	Snow Plow Package (lbs.)
		Minimum	Maximum			
Regular Cab 4x2/141.6	6.2L	3,800	3,950	1 UP	2 UP	---
	7.3L	3,800	3,950	1 UP	2 UP	---
	6.7L	4,400	4,550	1 UP	2 UP	---
Regular Cab 4x4/141.6	6.2L	4,400	4,400	1 UP	1 UP	5,600
	7.3L	4,400	4,400	1 UP	1 UP	5,600
	6.7L	4,800	5,200	1 UP	1 UP	6,000
SuperCab 4x2/148.0	6.2L	3,950	4,250	1 UP	2 UP	---
	7.3L	3,950	4,250	1 UP	2 UP	---
	6.7L	4,550	4,700	1 UP	2 UP	---
SuperCab 4x2/164.2	6.2L	4,250	4,400	1 UP	2 UP	---
	7.3L	4,250	4,400	1 UP	2 UP	---
	6.7L	4,850	5,000	1 UP	2 UP	---
SuperCab 4x4/148.0	6.2L	4,400	4,800	1 UP	1 UP	5,600
	7.3L	4,400	4,800	1 UP	1 UP	5,600
	6.7L	4,800	5,200	1 UP	1 UP	6,000
SuperCab 4x4/164.2	6.2L	4,800	4,800	1 UP	1 UP	6,000
	7.3L	4,800	4,800	1 UP	1 UP	6,000
	6.7L	5,200	5,600	1 UP	1 UP	6,000
Crew Cab 4x2/159.8	6.2L	4,100	4,250	1 UP	2 UP	---
	7.3L	4,100	4,250	1 UP	2 UP	---
	6.7L	4,550	4,850	1 UP	2 UP	---
Crew Cab 4x2/176.0	6.2L	4,400	4,700	1 UP	2 UP	---
	7.3L	4,400	4,700	1 UP	2 UP	---
	6.7L	5,000	5,250	1 UP	2 UP	---
Crew Cab 4x4/159.8	6.2L	4,400	4,800	1 UP	1 UP	6,000
	7.3L	4,400	4,800	1 UP	1 UP	6,000
	6.7L	5,200	5,600	1 UP	1 UP	6,000
Crew Cab 4x4/176.0	6.2L	4,800	5,200	1 UP	1 UP	6,000
	7.3L	4,800	5,200	1 UP	1 UP	6,000
	6.7L	5,600	5,600	1 UP	1 UP	6,000

F-350 SRW Pickup — Standard/Optional GVWR for 18" Wheel & Tire

Cab Style Drive/WB (in.)	Engine	Front GAWR (lbs.) Standard		Heavy-Duty Front Suspension Package (lbs.) 5,250-lb. Maximum (4x2) 6,000-lb. Maximum (4x4)	Camper Package (lbs.) 5,250-lb. Maximum (4x2) 6,000-lb. Maximum (4x4)	Snow Plow Package (lbs.)
		Minimum	Maximum			
Regular Cab 4x2/141.6	6.2L	3,950	3,950	1 UP	2 UP	---
	7.3L	3,950	3,950	1 UP	2 UP	---
	6.7L	4,550	4,550	1 UP	2 UP	---
Regular Cab 4x4/141.6	6.2L	4,400	4,400	1 UP	1 UP	5,600
	7.3L	4,400	4,400	1 UP	1 UP	5,600
	6.7L	5,200	5,200	1 UP	1 UP	6,000
SuperCab 4x2/148.0	6.2L	3,950	4,250	1 UP	2 UP	---
	7.3L	3,950	4,250	1 UP	2 UP	---
	6.7L	4,550	4,700	1 UP	2 UP	---
SuperCab 4x2/164.2	6.2L	4,250	4,550	1 UP	2 UP	---
	7.3L	4,250	4,550	1 UP	2 UP	---
	6.7L	4,850	5,000	1 UP	2 UP	---
SuperCab 4x4/148.0	6.2L	4,400	4,800	1 UP	1 UP	5,600
	7.3L	4,400	4,800	1 UP	1 UP	5,600
	6.7L	5,200	5,200	1 UP	1 UP	6,000
SuperCab 4x4/164.2	6.2L	4,800	4,800	1 UP	1 UP	6,000
	7.3L	4,800	4,800	1 UP	1 UP	6,000
	6.7L	5,200	5,600	1 UP	1 UP	6,000
Crew Cab 4x2/159.8	6.2L	4,100	4,250	1 UP	2 UP	---
	7.3L	4,100	4,250	1 UP	2 UP	---
	6.7L	4,700	4,850	1 UP	2 UP	---
Crew Cab 4x2/176.0	6.2L	4,400	4,700	1 UP	2 UP	---
	7.3L	4,400	4,700	1 UP	2 UP	---
	6.7L	5,000	5,250	1 UP	2 UP	---
Crew Cab 4x4/159.8	6.2L	4,400	4,800	1 UP	1 UP	6,000
	7.3L	4,400	4,800	1 UP	1 UP	6,000
	6.7L	5,200	5,600	1 UP	1 UP	6,000
Crew Cab 4x4/176.0	6.2L	4,800	5,200	1 UP	1 UP	6,000
	7.3L	4,800	5,200	1 UP	1 UP	6,000
	6.7L	5,600	5,600	1 UP	1 UP	6,000

F-350 SRW Pickup — 11,400 lb. GVWR

Cab Style Drive/WB (in.)	Engine	Front GAWR (lbs.) Standard		Heavy-Duty Front Suspension Package (lbs.) 5,250-lb. Maximum (4x2) 6,000-lb. Maximum (4x4)	Camper Package (lbs.) 5,250-lb. Maximum (4x2) 6,000-lb. Maximum (4x4)	Snow Plow Package (lbs.)
		Minimum	Maximum			
Regular Cab 4x4/141.6	6.2L	---	---	---	---	---
	7.3L	---	---	---	---	---
	6.7L	4,800	5,200	1 UP	1 UP	6,000
SuperCab 4x2/164.2	6.2L	---	---	---	---	---
	7.3L	---	---	---	---	---
	6.7L	4,850	5,000	1 UP	2 UP	---
SuperCab 4x4/148.0	6.2L	---	---	---	---	---
	7.3L	---	---	---	---	---
	6.7L	5,200	5,200	1 UP	1 UP	6,000
SuperCab 4x4/164.2	6.2L	4,800	5,200	1 UP	1 UP	6,000
	7.3L	4,800	5,200	1 UP	1 UP	6,000
	6.7L	5,600	5,600	1 UP	1 UP	6,000
Crew Cab 4x2/176.0	6.2L	---	---	---	---	---
	7.3L	---	---	---	---	---
	6.7L	5,000	5,250	1 UP	2 UP	---
Crew Cab 4x4/159.8	6.2L	---	---	---	---	---
	7.3L	---	---	---	---	---
	6.7L	5,200	5,600	1 UP	1 UP	6,000
Crew Cab 4x4/176.0	6.2L	5,200	5,200	1 UP	1 UP	6,000
	7.3L	5,200	5,200	1 UP	1 UP	6,000
	6.7L	5,600	5,600	1 UP	1 UP	6,000

Please refer to the Body Builder's Layout Book for further information regarding front GAWR.

2020 SUPER DUTY F-SERIES TRUCKS

Front GAWR Selection Chart

9/23/2019

The standard front spring/GAWR(1) on pickup models is computer selected based on the total front weight of options ordered. Front spring/GAWR upgrades are in increments of 150 lbs. on 4x2 models with spring ratings from 3,800 lbs. to 5,250 lbs. and in increments of 400 lbs. on 4x4 models with spring ratings from 4,400 lbs. to 6,000 lbs. Certain option packages include the following front spring/GAWR upgrades:

F-350 DRW Pickup

Heavy-Service Suspension Package	Front springs/GAWR will be selected 1 upgrade higher than standard computer selection.
Camper Package	4x2: Front springs/GAWR will be selected 2 upgrades higher than standard computer selection.
	4x4: Front springs/GAWR will be selected 1 upgrade higher than standard computer selection.
Snow Plow Package	Front springs/GAWR is assigned or specifically selected as shown in the chart below.

Front spring/GAWR upgrade is not included if the maximum front spring has been computer selected as a consequence of options ordered.

Cab Style Drive/WB (in.)	Engine	Front GAWR (lbs.) Standard		Heavy-Duty Front Suspension Package (lbs.) 5,250-lb. Maximum (4x2) 6,000-lb. Maximum (4x4)	Camper Package (lbs.) 5,250-lb. Maximum (4x2) 6,000-lb. Maximum (4x4)	Snow Plow Package (lbs.)
		Minimum	Maximum			
Regular Cab 4x2/141.6	6.2L	4,100	4,100	1 UP	2 UP	---
	7.3L	4,100	4,100	1 UP	2 UP	---
	6.7L	4,550	4,700	1 UP	2 UP	---
Regular Cab 4x4/141.6	6.2L	4,400	4,800	1 UP	1 UP	5,600
	7.3L	4,400	4,800	1 UP	1 UP	5,600
	6.7L	5,200	5,200	1 UP	1 UP	6,000
SuperCab 4x2/164.2	6.2L	4,400	4,550	1 UP	2 UP	---
	7.3L	4,400	4,550	1 UP	2 UP	---
	6.7L	5,000	5,250	1 UP	2 UP	---
SuperCab 4x4/164.2	6.2L	4,800	5,200	1 UP	1 UP	6,000
	7.3L	4,800	5,200	1 UP	1 UP	6,000
	6.7L	5,600	5,600	1 UP	1 UP	6,000
Crew Cab 4x2/176.0	6.2L	4,550	4,700	1 UP	2 UP	---
	7.3L	4,550	4,700	1 UP	2 UP	---
	6.7L	5,250	5,250	1 UP	2 UP	---
Crew Cab 4x4/176.0	6.2L	5,200	5,200	1 UP	1 UP	6,000
	7.3L	5,200	5,200	1 UP	1 UP	6,000
	6.7L	5,600	5,600	1 UP	1 UP	6,000

F-350 DRW Pickup — 13,000 lbs. GVWR

Cab Style Drive/WB (in.)	Engine	Front GAWR (lbs.) Standard		Heavy-Duty Front Suspension Package (lbs.) 5,250-lb. Maximum (4x2) 6,0000-lb. Maximum (4x4)		Snow Plow Package (lbs.)
		Minimum	Maximum			
Regular Cab 4x2/141.6	6.2L	3,950	4,100	1 UP	2 UP	---
	7.3L	3,950	4,100	1 UP	2 UP	---
	6.7L	4,550	4,700	1 UP	2 UP	---
Regular Cab 4x4/141.6	6.2L	4,400	4,400	1 UP	1 UP	5,600
	7.3L	4,400	4,400	1 UP	1 UP	5,600
	6.7L	5,200	5,200	1 UP	1 UP	6,000
SuperCab 4x2/164.2	6.2L	4,400	4,550	1 UP	2 UP	---
	7.3L	4,400	4,550	1 UP	2 UP	---
	6.7L	5,000	5,250	1 UP	2 UP	---
SuperCab 4x4/164.2	6.2L	4,800	5,200	1 UP	1 UP	6,000
	7.3L	4,800	5,200	1 UP	1 UP	6,000
	6.7L	5,600	5,600	1 UP	1 UP	6,000
Crew Cab 4x2/176.0	6.2L	4,550	4,700	1 UP	2 UP	---
	7.3L	4,550	4,700	1 UP	2 UP	---
	6.7L	5,250	5,250	1 UP	2 UP	---
Crew Cab 4x4/176.0	6.2L	4,800	5,200	1 UP	1 UP	6,000
	7.3L	4,800	5,200	1 UP	1 UP	6,000
	6.7L	5,600	5,600	1 UP	1 UP	6,000

(1) Gross Axle Weight Rating is determined by the rated capacity of the minimum component of the axle system (axle, computer-selected springs, wheels, tires) of a specific vehicle. Front and rear GAWRs will, in all cases, sum to a number equal to or greater than the GVWR for the particular vehicle. Maximum loaded vehicle (including passengers, equipment and payload) cannot exceed the GVW rating or GAWR (front or rear).

Please refer to the Body Builder's Layout Book for further information regarding front GAWR.

2020 SUPER DUTY F-SERIES TRUCKS

Front GAWR Selection Charts

9/23/2019

F-450 Pickup — Standard GVWR

Cab Style Drive/WB (in.)	Engine	Front GAWR (lbs.) Standard		Heavy-Duty Front Suspension Package (lbs.) 1 UP	Camper Package (lbs.) 1 UP	Snow Plow Package (lbs.)
		Minimum	Maximum			
Regular Cab 4x2/141.6	6.7L	5,200	5,200	1 UP	2 UP	–
Regular Cab 4x4/141.6	6.7L	5,200	5,600	1 UP	1 UP	6,000
Crew Cab 4x2/176.0	6.7L	5,600	5,600	6,000	6,000	–
Crew Cab 4x4/176.0	6.7L	5,600	6,000	6,000	6,000	6,000

2020 SUPER DUTY F-SERIES TRUCKS

Front GAWR Selection Charts

9/23/2019

F-350 SRW Chassis Cabs — Standard GVWR

Cab Style Drive/WB (in.)	Engine	GVWR Standard (lbs.)	Front GAWR Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[1] (lbs.)	Snow Plow Package (lbs.)
Regular Cab 4x2/145.3	6.2L	9,800	4,100	4,400	4,550	---	---	---
	7.3L	9,800	4,100	4,250	4,400	---	---	---
	6.7L	9,800	4,700	4,850	5,000	5,250	5,250	---
Regular Cab 4x4/145.3	6.2L	9,800	4,400	4,800	5,200	---	---	5,600
	7.3L	9,800	4,400	4,800	5,200		---	5,600
	6.7L	9,800	5,200	5,600	5,990	5,990	5,990	5,990
SuperCab 4x2/167.9	6.2L	9,800	4,400	4,550	4,700	---	---	---
	7.3L	9,800	4,400	4,550	4,700	---	---	---
	6.7L	9,800	5,250	5,250	5,250	5,250	5,250	---
SuperCab 4x4/167.9	6.2L	9,800	4,800	5,200	5,600	---	---	5,990
	7.3L	9,800	4,800	5,200	5,600	---	---	5,990
	6.7L	9,800	5,600	5,990	5,990	5,990	5,990	5,990
Crew Cab 4x2/179.8	6.2L	9,800	4,550	4,700	4,850	----	---	---
	7.3L	9,800	4,550	4,700	4,850	---	---	---
	6.7L	9,800	5,250	5,250	5,250	5,250	5,250	---
Crew Cab 4x4/179.8	6.2L	9,800	5,200	5,600	5,990	---	---	5,990
	7.3L	9,800	5,200	5,600	5,990	---	---	5,990
	6.7L	9,800	5,600	5,990	5,990	5,990	5,990	5,990

F-350 SRW Chassis Cabs — 10,000-lb. GVWR

Cab Style Drive/WB (in.)	Engine	GVWR Standard (lbs.)	Front GAWR Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[1] (lbs.)	Snow Plow Package (lbs.)
Regular Cab 4x2/145.3	6.2L	10,000	4,100	4,250	4,400	---	---	---
	7.3L	10,000	4,100	4,250	4,400	---	---	---
	6.7L	10,000	4,700	4,850	5,000	5,250	5,250	---
Regular Cab 4x4/145.3	6.2L	10,000	4,400	4,800	5,200	---	---	5,600
	7.3L	10,000	4,400	4,800	5,200	---	---	5,600
	6.7L	10,000	5,200	5,600	5,990	5,990	5,990	5,990
SuperCab 4x2/167.9	6.2L	10,000	4,400	4,550	4,700	---	---	---
	7.3L	10,000	4,400	4,550	4,700	---	---	---
	6.7L	10,000	5,250	5,250	5,250	5,250	5,250	---
SuperCab 4x4/167.9	6.2L	10,000	4,800	5,200	5,600	----	----	5,990
	7.3L	10,000	4,800	5,200	5,600	---	---	5,990
	6.7L	10,000	5,600	5,990	5,990	5,990	5,990	5,990
Crew Cab 4x2/179.8	6.2L	10,000	4,550	4,700	4,850	---	---	---
	7.3L	10,000	4,550	4,700	4,850	---	---	---
	6.7L	10,000	5,250	5,250	5,250	5,250	5,250	---
Crew Cab 4x4/179.8	6.2L	10,000	5,200	5,600	5,990	---	---	5,990
	7.3L	10,000	5,200	5,600	5,990	---	---	5,990
	6.7L	10,000	5,600	5,990	5,990	5,990	5,990	5,990

F-350 SRW Chassis Cabs — Variable GVWR

Cab Style Drive/WB (in.)	Engine	GVWR (lbs.)	Front GAWR Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[1] (lbs.)	Snow Plow Package (lbs.)
Regular Cab 4x2/145.3	6.2L	10,500	3,950	4,100	4,250	---	---	---
	7.3L	10,500	3,950	4,100	4,250	---	---	---
	6.7L	11,100	4,550	4,700	4,850	5,250	5,250	---
Regular Cab 4x4/145.3	6.2L	10,900	4,400	4,800	5,200	---	---	5,600
	7.3L	10,900	4,400	4,800	5,200	---	---	5,600
	6.7L	11,500	5,200	5,600	5,990	5,990	5,990	5,990
SuperCab 4x2/167.9	6.2L	10,900	4,400	4,550	4,700	---	---	---
	7.3L	10,900	4,400	4,550	4,700	---	---	---
	6.7L	11,500	5,000	5,250	5,250	5,250	5,250	---
SuperCab 4x4/167.9	6.2L	11,300	4,800	5,200	5,600	---	---	5,990
	7.3L	11,300	4,800	5,200	5,600	---	---	5,990
	6.7L	11,500	5,600	5,990	5,990	5,990	5,990	5,990
Crew Cab 4x2/179.8	6.2L	11,000	4,550	4,700	4,850	---	---	---
	7.3L	11,000	4,550	4,700	4,850	---	---	---
	6.7L	11,500	5,000	5,250	5,250	5,250	5,250	---
Crew Cab 4x4/179.8	6.2L	11,400	4,800	5,200	5,600	---	---	5,990
	7.3L	11,400	4,800	5,200	5,600	---	---	5,990
	6.7L	11,500	5,600	5,990	5,990	5,990	5,990	5,990

(1) Ford vehicles equipped with the Fire/Rescue Prep Package with Special Emissions — for Diesel Engine (47J) NOT completed as Emergency Vehicles as defined per 40 CFR 86.1803.01 in the Federal Register **voids** the Ford Warranty.

2020 SUPER DUTY F-SERIES TRUCKS

Front GAWR Selection Charts

9/23/2019

F-350 DRW Chassis Cabs

Cab Style Drive/WB (in.)	Engine	GVWR (lbs.)	Front GAWR Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[(1)] (lbs.)	Snow Plow Package (lbs.)
Regular Cab 4x2/145.3	6.2L	14,000	4,250	4,400	4,550	---	---	---
	7.3L	14,000	4,250	4,400	4,550	---	---	---
	6.7L	14,000	4,850	5,000	5,250	5,250	5,250	---
Regular Cab 4x2/169.3	6.2L	14,000	4,700	4,850	5,000	---	---	---
	7.3L	14,000	4,700	4,850	5,000	---	---	---
	6.7L	14,000	5,250	5,250	5,250	5,250	5,250	---
Regular Cab 4x4/145.3	6.2L	14,000	4,800	5,200	5,600	---	---	5,990
	7.3L	14,000	4,800	5,200	5,600	---	---	5,990
	6.7L	14,000	5,200	5,600	5,990	5,990	5,990	5,990
Regular Cab 4x4/169.3	6.2L	14,000	5,200	5,600	5,990	---	---	5,990
	7.3L	14,000	5,200	5,600	5,990	---	---	5,990
	6.7L	14,000	5,600	5,990	5,990	5,990	5,990	5,990
SuperCab 4x2/167.9	6.2L	14,000	4,550	4,700	4,850	---	---	---
	7.3L	14,000	4,550	4,700	4,850	---	---	---
	6.7L	14,000	5,250	5,250	5,250	5,250	5,250	---
SuperCab 4x4/167.9	6.2L	14,000	5,200	5,600	5,990	---	---	5,990
	7.3L	14,000	5,200	5,600	5,990	---	---	5,990
	6.7L	14,000	5,600	5,990	5,990	5,990	5,990	5,990
Crew Cab 4x2/179.8	6.2L	14,000	4,700	4,850	5,000	---	---	---
	7.3L	14,000	4,700	4,850	5,000	---	---	---
	6.7L	14,000	5,250	5,250	5,250	5,250	5,250	---
Crew Cab 4x4/179.8	6.2L	14,000	5,200	5,600	5,990	---	---	5,990
	7.3L	14,000	5,200	5,600	5,990	---	---	5,990
	6.7L	14,000	5,600	5,990	5,990	5,990	5,990	5,990

(1) Ford vehicles equipped with the Fire/Rescue Prep Package with Special Emissions — for Diesel Engine (47J) NOT completed as Emergency Vehicles as defined per 40 CFR 86.1803.01 in the Federal Register **voids** the Ford Warranty.

2020 SUPER DUTY F-SERIES TRUCKS
Front GAWR Selection Charts
9/23/2019

F-450 Chassis Cabs — Standard 16,500-lb. & Optional 16,000-/15,000-lb. GVWR

Cab Style Drive/WB (in.)	Engine	GVWR Standard/Opt./Opt. (lbs.)	Front GAWR Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[1] (lbs.)	Wrecker Package (lbs.)	Snow Plow Package (lbs.)	Extra Heavy-Duty Front End Suspension[2] (lbs.)
Regular Cab 4x2/145.3	7.3L	16,500/16,000/15,000	4,800	5,200	5,600	----	----	7,000	6,500	7,500
	6.7L	16,500/16,000/15,000	5,200	5,600	6,000	7,000	7,000	7,000	7,000	7,500
Regular Cab 4x2/169.3	7.3L	16,500/16,000/15,000	5,200	5,600	6,000	----	----	----	6,500	7,500
	6.7L	16,500/16,000/15,000	6,000/5,600/5,600	6,500/6,000/6,000	7,000/6,500/6,500	7,000	7,000	----	7,000	7,500
Regular Cab 4x2/193.3	7.3L	16,500/16,000/15,000	5,600	6,000	6,500	----	----	----	6,500	7,500
	6.7L	16,500/16,000/15,000	6,500/6,000/6,000	7,000/6,500/6,500	7,000	7,000	7,000	----	7,000	7,500
Regular Cab 4x2/205.3	7.3L	16,500/16,000/15,000	6,000/5,600/5,600	6,500/6,000/6,000	7,000/6,500/6,500	----	----	----	6,500	7,500
	6.7L	16,500/16,000/15,000	6,500	7,000	7,000	7,000	7,000	----	7,000	7,500
Regular Cab 4x4/145.3	7.3L	16,500/16,000/15,000	4,800	5,200	5,600	----	----	7,000	6,500	7,500
	6.7L	16,500/16,000/15,000	5,600	6,000	6,500	7,000	7,000	7,000	7,000	7,500
Regular Cab 4x4/169.3	7.3L	16,500/16,000/15,000	5,600/5,600/5,200	6,000/6,000/5,600	6,500/6,500/6,000	----	----	----	6,500	7,500
	6.7L	16,500/16,000/15,000	6,000	6,500	7,000	7,000	7,000	----	7,000	7,500
Regular Cab 4x4/193.3	7.3L	16,500/16,000/15,000	6,000	6,500	7,000	----	----	----	7,000	7,500
	6.7L	16,500/16,000/15,000	6,500	7,000	7,000	7,000	7,000	----	7,000	7,500
Regular Cab 4x4/205.3	7.3L	16,500/16,000/15,000	6,000	6,500	7,000	----	----	----	7,000	7,500
	6.7L	16,500/16,000/15,000	6,500	7,000	7,000	7,000	7,000	----	7,000	7,500
SuperCab 4x2/167.9	7.3L	16,500/16,000/15,000	5,200/5,200/4,800	5,600/5,600/5,200	6,000/6,000/5,600	----	----	----	6,500	7,500
	6.7L	16,500/16,000/15,000	5,600	6,000	6,500	7,000	7,000	----	7,000	7,500
SuperCab 4x2/191.9	7.3L	16,500/16,000/15,000	5,600	6,000	6,500	----	----	----	6,500	7,500
	6.7L	16,500/16,000/15,000	6,000	6,500	7,000	7,000	7,000	----	7,000	7,500
SuperCab 4x4/167.9	7.3L	16,500/16,000/15,000	5,200	5,600	6,000	----	----	----	7,000	7,500
	6.7L	16,500/16,000/15,000	6,000	6,500	7,000	7,000	7,000	----	7,000	7,500
SuperCab 4x4/191.9	7.3L	16,500/16,000/15,000	6,000/6,000/5,600	6,500/6,500/6,000	7,000/7,000/6,500	----	----	----	7,000	7,500
	6.7L	16,500/16,000/15,000	6,500	7,000	7,000	7,000	7,000	----	7,000	7,500
Crew Cab 4x2/179.8	7.3L	16,500/16,000/15,000	5,200	5,600	6,000	----	----	----	6,500	7,500
	6.7L	16,500/16,000/15,000	5,600	6,000	6,500	7,000	7,000	----	7,000	7,500
Crew Cab 4x2/203.8	7.3L	16,500/16,000/15,000	5,600	6,000	6,500	----	----	----	6,500	7,500
	6.7L	16,500/16,000/15,000	6,500/6,000/6,000	7,000/6,500/6,500	7,000	7,000	7,000	----	7,000	7,500
Crew Cab 4x4/179.8	7.3L	16,500/16,000/15,000	5,200	5,600	6,000	----	----	----	7,000	7,500
	6.7L	16,500/16,000/15,000	6,000	6,500	7,000	7,000	7,000	----	7,000	7,500
Crew Cab 4x4/203.8	7.3L	16,500/16,000/15,000	6,000/6,000/5,600	6,500/6,500/6,000	7,000/7,000/6,500	----	----	----	7,000	7,500
	6.7L	16,500/16,000/15,000	6,500	7,000	7,000	7,000	7,000	----	7,000	7,500

(1) Ford vehicles equipped with the Fire/Rescue Prep Package with Special Emissions — for Diesel Engine (47J) NOT completed as Emergency Vehicles as defined per 40 CFR 86.1803.01 in the Federal Register **voids** the Ford Warranty.
(2) Requires 4.30 or 4.88 axle ratio.

2020 SUPER DUTY F-SERIES TRUCKS
Front GAWR Selection Charts
9/23/2019

F-550 Chassis Cabs — Standard/Optional GVWR

Cab Style Drive/WB (in.)	Engine	GVWR Standard/Opt./Opt. (lbs.)	Front GAWR Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package[1] (lbs.)	Snow Plow Package (lbs.)	Extra Heavy-Duty Front End Suspension[2] (lbs.)
Regular Cab 4x2/145.3	6.8L	18,000/17,500/19,000	4,800/4,800/5,600	5,200/5,200/6,000	5,600/5,600/6,500	----	----	6,500	7,500
	6.7L	18,000/17,500/19,500	5,200	5,600	6,000	7,000	7,000	7,000	7,500
Regular Cab 4x2/169.3	6.8L	18,000/17,500/19,500	5,600/5,200/5,600	6,000/5,600/6,000	6,500/6,000/6,500	----	----	6,500	7,500
	6.7L	18,000/17,500/19,500	6,000	6,500	7,000	7,000	7,000	7,000	7,500
Regular Cab 4x2/193.3	6.8L	18,000/17,500/19,500	6,000	6,500	7,000	----	----	6,500	7,500
	6.7L	18,000/17,500/19,500	6,500/6,500/7,000	7,000	7,000	7,000	7,000	7,000	7,500
Regular Cab 4x2/205.3	6.8L	18,000/17,500/19,500	6,000/6,000/6,500	6,500/6,500/7,000	7,000	----	----	6,500	7,500
	6.7L	18,000/17,500/19,500	6,500/6,500/7,000	7,000	7,000	7,000	7,000	7,000	7,500
Regular Cab 4x4/145.3	6.8L	18,000/17,500/19,000	5,200/5,200/5,600	5,600/5,600/6,000	6,000/6,000/6,500	----	----	7,000	7,500
	6.7L	18,000/17,500/19,500	5,600	6,000	6,500	7,000	7,000	7,000	7,500
Regular Cab 4x4/169.3	6.8L	18,000/17,500/19,500	5,600	6,000	6,500	----	----	7,000	7,500
	6.7L	18,000/17,500/19,500	6,500/6,000/6,500	7,000/6,500/7,000	7,000	7,000	7,000	7,000	7,500
Regular Cab 4x4/193.3	6.8L	18,000/17,500/19,500	6,500/6,000/6,500	7,000/6,500/7,000	7,000	----	----	7,000	7,500
	6.7L	18,000/17,500/19,500	7,000	7,000	7,000	7,000	7,000	7,000	7,500
Regular Cab 4x4/205.3	6.8L	18,000/17,500/19,500	6,500	7,000	7,000	----	----	7,000	7,500
	6.7L	18,000/17,500/19,500	7,000	7,000	7,000	7,000	7,000	7,000	7,500
SuperCab 4x2/167.9	6.8L	18,000/17,500/19,500	5,200	5,600	6,000	----	----	6,500	7,500
	6.7L	18,000/17,500/19,500	5,600	6,000	6,500	7,000	7,000	7,000	7,500
SuperCab 4x2/191.9	6.8L	18,000/17,500/19,500	5,600/6,500/6,000	6,000/6,000/6,500	6,500/6,500/7,000	----	----	6,500	7,500
	6.7L	18,000/17,500/19,500	6,500	7,000	7,000	7,000	7,000	7,000	7,500
SuperCab 4x4/167.9	6.8L	18,000/17,500/19,500	5,200/5,200/5,600	5,600/5,600/6,000	6,000/6,000/6,500	----	----	7,000	7,500
	6.7L	18,000/17,500/19,500	6,000	6,500	7,000	7,000	7,000	7,000	7,500
SuperCab 4x4/191.9	6.8L	18,000/17,500/19,500	6,000	6,500	7,000	----	----	7,000	7,500
	6.7L	18,000/17,500/19,500	6,500	7,000	7,000	7,000	7,000	7,000	7,500
Crew Cab 4x2/179.8	6.8L	18,000/17,500/19,500	5,200	5,600	6,000	----	----	6,500	7,500
	6.7L	18,000/17,500/19,500	5,600/5,600/6,000	6,000/6,000/6,500	6,500/6,500/7,000	7,000	7,000	7,000	7,500
Crew Cab 4x2/203.8	6.8L	18,000/17,500/19,500	5,600/5,600/6,000	6,000/6,000/6,500	6,500/6,500/7,000	----	----	6,500	7,500
	6.7L	18,000/17,500/19,500	6,500	7,000	7,000	7,000	7,000	7,000	7,500
Crew Cab 4x4/179.8	6.8L	18,000/17,500/19,500	5,600	6,000	6,500	----	----	7,000	7,500
	6.7L	18,000/17,500/19,500	6,000	6,500	7,000	7,000	7,000	7,000	7,500
Crew Cab 4x4/203.8	6.8L	18,000/17,500/19,500	6,000	6,500	7,000	----	----	7,000	7,500
	6.7L	18,000/17,500/19,500	6,500	7,000	7,000	7,000	7,000	7,000	7,500

(1) Ford vehicles equipped with the Fire/Rescue Prep Package with Special Emissions — for Diesel Engine (47J) NOT completed as Emergency Vehicles as defined per 40 CFR 86.1803.01 in the Federal Register **voids** the Ford Warranty.
(2) Requires 4.30 or 4.88 axle ratio.